

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. - 7. (Canceled).

8. (Currently Amended) A server apparatus comprising:

a network process unit configured to connect an electronic apparatus, which transmits/receives data via a first network, to a second network through the server apparatus; and

an AV function unit configured to process video data and sound data;

the network process unit switching an operation of the AV function unit between a normal operation mode and a standby mode serving to reduce power consumption, when the network process unit receives, from the electronic apparatus, a communication packet containing a command requesting that the operation of the AV function unit be changed.

9. (Previously Presented) The server apparatus according to claim 8, wherein, upon switching of operation of the AV function unit, the network process unit notifies the electronic apparatus that the operation of the AV function unit has been switched.

10. - 13. (Canceled).

14. (Previously Presented) A server apparatus comprising:

a network process unit configured to connect an electronic apparatus, which transmits/receives data via a first network, to a second network through the server apparatus; and

an AV function unit configured to process video data and sound data,

the network process unit including:

a detecting unit configured to detect a power supply control packet in communication packets sent from the electronic apparatus, the power supply control packet containing a power-on command for causing the AV function unit to recover from a standby mode serving to reduce power consumption or a power supply standby command for causing the AV function unit to shift to the standby mode; and

a controlling unit configured to cause the AV function unit to recover from or shift to the standby mode, when the detecting unit detects the power supply control packet.

15. (New) The server apparatus according to claim 14, further comprising:

an embedded controller configured to control power supply to the AV function unit for interrupting the power supply; and

an up/down signal line which is arranged between the network process unit and the embedded controller,

the controlling unit of the network process unit outputting an up/down signal providing an instruction to supply power to the AV function unit or to interrupt the power supply on the up/down signal line.

16. (New) The server apparatus according to claim 15, further comprising:

a status signal line which is arranged between the network process unit and the embedded controller,

the embedded controller being configured to output a status signal indicating a status of the AV function unit on the status signal line.